


## BIP-10

## BIP-12

### BIP-10



#### Mechanical

Recommended Travel:	.126 (3.20)
Full Travel:	.157 (4.00)
Operating Temperature:	-40°C to +80°C

#### Spring Force in oz. (grams)

	Preload	Rec. Travel
<b>Standard</b>	1.00 (28.3)	5.40 (153)


#### Electrical (Static Conditions)

Current Rating:	5 amps
Average Probe Resistance:	<30 mOhms, Steel, Gold plated <100 mOhms, Stainless Steel

#### Materials and Finishes

Plunger:	Brass, Gold plated
Barrel:	Brass, Gold plated
Spring:	Steel, Gold plated or Stainless

### BIP-12



#### Mechanical

Recommended Travel:	.315 (8.00)
Full Travel:	.374 (10.00)
Operating Temperature:	-40°C to +80°C

#### Spring Force in oz. (grams)

	Preload	Rec. Travel
<b>Standard</b>	0.87 (24.7)	5.40 (153)

#### Electrical (Static Conditions)

Current Rating:	5 amps
Average Probe Resistance:	<30 mOhms, Steel, Gold plated <100 mOhms, Stainless Steel

#### Materials and Finishes

Plunger:	BeCu, Gold plated
Barrel:	Brass, Gold plated
Spring:	Steel, Gold plated or Stainless

Dimensions in inches (millimeters). Specifications subject to change without notice.  
Consult factory for other temperature requirements, and applications below -40°C.  
Stocking Disclaimer: Stocking levels for part numbers listed in this catalog are subject to change.  
Availability is based on current levels of usage and demand.



ECT-CPG.com  
shop.ECT-CPG.com